



demma 德玛
www.demma.com.cn

demma

分线盒
Distribution box

单极分线盒
Unipolar splitter box


demma 德玛

认证 CE RoHS | 材料 PA66 | IP等级 IP20

DMK80A



型号:DMK80A
订货号:10120006001
表面处理:电镀及本色
I=80 A IEC 60947-7-1
I=50 Amp UL/CSA
Icw KA rms is:3
Ipk KA:22
Ui:690V ICE
Vin:600 V UL
安装孔距:54mm
模块化:单股进线,可用跳线进行扩展,可双倍中性线




公制	mm²		Γ (N.m)
	6...16	x1	2.5
	2.5...6	x4	1.8
	2.5...16	x2	2.5
美规	AMG		力矩
	16...4	x1	17.5
	16...8	x4	10.6
	16...4	x2	17.5

DMK125A



型号:DMK125A
订货号:10120006002
表面处理:电镀及本色
I=125 A IEC 60947-7-1
I=150 Amp UL/CSA
Icw KA rms is:4.2
Ipk KA:30
Ui:690V IEC
Vin:600 V UL
安装孔距:64mm
模块化:单股进线,可用跳线进行扩展,可双倍中性线




**或通用跳线			
公制	mm²		Γ (N.m)
	10...35	x1	4
	6...16**	x4	2.5
	2.5...16	x6	2.5
美规	AMG		力矩
	8...1/0	x1	35
	14...4	x4	17.5
	14...4	x6	17.5

DMK160A



型号:DMK160A
订货号:10120006003
表面处理:电镀及本色
I=160 A IEC 60947-7-1
I=200 Amp UL/CSA
Icw KA rms is:11.8
Ipk KA:30
Ui:690V IEC
Vin:600 V UL
安装孔距:64mm
模块化:单股进线,可用跳线进行扩展,可双倍中性线



**或通用跳线			
公制	mm²		Γ (N.m)
	10...70	x1	5.5
	6...16**	x1	2.5
	2.5...16	x6	2.5
美规	AMG		力矩
	8...3/0	x1	56
	16...8	x1	17.5
	16...4	x6	17.5

单极分线盒

Unipolar splitter box

认证  RoHS | 材料 PA66 | IP等级 IP20

DMK250A



型号:DMK250A
订货号:10120006004
表面处理:电镀及本色
I=250 A IEC 60947-7-1
I=255 Amp UL/CSA
Icw KA rms is:24.5
Ipk KA:51
Ui:690V ICE
Vin:600 V UL
安装孔距:85X29mm
模块化:允许多种组合,可用于单极、两级、三级、四级

用TF 250A与TH柔性母排连接		公制		mm ²	mm ²		Γ(N.m)
		35...120	35...120	x1			16
		6...35	6...35	x2			4.0
		2.5...16	2.5...16	x5			2.7
		2.5...10	2.5...10	x4			2.5
美规		AMG					力矩
		6...250 Kcmil	x1				201
		14...1	x2				35
		14...4	x5				24
		14...6	x4				17.5

DMK400A



型号:DMK400A
订货号:10120006005
表面处理:电镀及本色
I=400 A IEC 60947-7-1
I=355 Amp UL/CSA
Icw KA rms is:24.5
Ipk KA:51
Ui:690V ICE
Vin:600 V UL
安装孔距:85x29mm
模块化:允许多种组合,可用于单极、两级、三级、四级

用TF 400A与TH柔性母排连接		公制		mm ²	mm ²		Γ(N.m)
		95...185		x1			20
		6...25	6...25	x2			4.0
		2.5...16	2.5...16	x5			2.7
		2.5...10	2.5...10	x4			2.5
美规		AMG					力矩
		3/0...400 Kcmil	x1				201
		14...1	x2				35
		14...4	x5				24
		14...6	x4				17.5

DMK500A



型号:DMK500A
订货号:10120006006
表面处理:电镀及本色
I=500 A IEC 60947-7-1
I=520 Amp UL/CSA
Icw KA rms is:24.5
Ipk KA:51
Ui:690V ICE
Vin:600 V UL
安装孔距:85X29mm
模块化:单股进线,可用跳线进行扩展,可双倍中性线


直接与TH柔性母排连接		公制		mm ²	mm ²		Γ(N.m)
		4x15.5x0.8...8x24x1	4x15.5x0.8...8x24x1				2.5
		6...35	6...25	x2			4.0
		2.5...16	2.5...16	x5			2.7
		2.5...10	2.5...10	x4			2.5
美规		AMG					力矩
		4x15.5x0.8...8x24x1					17.5
		14...1	x2				35
		14...4	x5				24
		14...6	x4				17.5

两极/四极分线盒


Two pole / four pole junction box

认证  RoHS | 材料 PA66 | IP等级 IP20


DMUK207




型号:DMUK207
2极 100A
订货号:10120006013
EN 60947-1
Icw kA rms ls:4.5
Ipk kA:20
Ui:500V



DMUK407




型号:DMUK407
4极 125A
订货号:10120006014
EN 60947-1
Icw kA rms ls:4.5
Ipk kA:20
Ui:500V



DMUK411



型号:DMUK411
4极 100A
订货号:10120006015
EN 60947-1
Icw kA rms ls:4.5
Ipk kA:20
Ui:500V



UK 207 100A-6端子

mm ²	mm ²	位数	Φ	Γ(N.m)
	10...35	10...25	x1	8.5
	1.5...4	0.75...4	x3	4.5
	2.5...6	1.5...6	x3	5.5

UK 207 100A-6端子

mm ²	mm ²	位数	Φ	Γ(N.m)
	10...35	10...35	x1	9.5
	2.5...6	1.5...6	x5	5.5
	10...25	6...16	x1	7.5


DMUK 411 100A-10端子

mm ²	mm ²	位数	Φ	Γ(N.m)
	10...35	10...25	x2	8.5
	1.5...4	0.75...4	x4	4.5
	2.5...6	1.5...6	x5	5.5

DMUK412




型号:DMUK412
4极 160A
订货号:10120006017
EN 60947-1
Icw kA rms ls:6
Ipk kA:22
Ui:600V



DMUK415



型号:DMUK415
4极 100A
订货号:10120006016
EN 60947-1
Icw kA rms ls:4.5
Ipk kA:20
Ui:500V



DMUK 412 160A-11端子

mm ²	mm ²	位数	Φ	Γ(N.m)
	10...50	10...50	x1	12
	10...35	10...25	x2	8.5
	2.5...16	1.5...16	x8	7

DMUK 415 100A-14端子

mm ²	mm ²	位数	Φ	Γ(N.m)
	10...35	10...25	x2	8.5
	1.5...4	0.75...4	x6	4.5
	2.5...6	1.5...6	x7	5.5